

## Close

The *Close* action closes an object (table, query, form or report).

tags:

Actions

### Applies to ...

Object	Description
DoCmd	Root class. When present, its name must be "DoCmd" but the object name is optional.

### Syntax

[DoCmd.]mClose(*ObjectType*, *ObjectName*, *Save*)

Argument	Optional	Type or Symbol	Description
ObjectType	No	acTable acQuery acForm acReport	The type of object to close.
ObjectName	No	String	The name of the object to close. This argument is NOT case-sensitive.
Save	Yes	acSavePrompt	Indicates if a prompt to the user will prevent from closing without saving. acSavePrompt is the only supported value.

The symbolic constants can be included in your code by copying and pasting next lines:

```
Const acForm = 2
Const acQuery = 1
Const acReport = 3
Const acTable = 0

Const acSavePrompt = 0
```

### Remarks

- The *ObjectName* object must exist in the database document (".odb" file). However if it is not open, the command has no effect.
- If the object is a table or a query, and the object is not open, running the *Close* action will open the Table or Query and close it immediately.
- The *Close* action is not allowed from a non-Base document containing **standalone forms**.

### Error messages

Table (or form or query or report) '...' could not be closed
Table (or form or query or report) '...' not found

### See also

OpenForm  
OpenQuery  
OpenReport  
OpenTable

### Example

```
mClose(acTable, "myTable")
```

Bookmark this page » » [Close](#)